

weldcote SUPREMEVIEW TRUE-COLOR

Digital Auto Darkening Helmet (High Definition Filter Optics)

NEW



16.3 square inches of viewing area!



Shade 3



Shade 13



- ADF Cartridge Size: 4.5 x 5.25"
- LCD Viewing Area: 4.04 x 4.04"

Press and hold external grind mode button for 2 seconds to switch to shade 3 for grind mode.



New Headgear as Standard



Knob & Grind Mode Button



Viewing Size:
102.5x102.5 mm / 4.04x4.04"
(16.3 Sq. Inches)



Dark Shade #:
5-9 / 9-13



Warranty:
3 Years



UV/IR Protection:
Up to DIN15



Power Supply:
ADF Battery:
CR2450 2-Pcs



Switching Time
(light to dark):
0.04ms

- **Optical Clarity Classification: 1/1/1/1**
- **Auto Shade on: Weldcote ShadeACC™ technology, automatically matches and sets the welding shade number according to the intensity of the ARC light. Our technology effectively protects the eyes and face while providing a clearer and more accurate weld.**
- The external button on the side can be shade adjusted in increments of 0.1 per adjustment, with a range of +2.0 ~ -2.0 per shade between shade ranges 7-13.
- Light State: Shade 3 • Dark State: Shade 5-9 / 9-13
- **Shade Range:** Manual mode: 3/5-13, Auto Mode: 3/7<13M
- **Auto shade manual mode. Change shade adjustment by external knob in increments of 0.5 shade.**
- Switching Time (light to dark): 0.04ms (ANSI)
- Delay Time (dark to light): Adjustable (1-5 for 0.1s – 0.9s)
- Sensitivity: Adjustable (1-5 for low-high)
- Arc Sensors: 4 • Ambient Light Sensor: 1
- Lock Shade: Yes • Grind Function: Yes; External
- Grinding Warning Flash: Yes

- **Minimum TIG Current: >2 amp**
- **Black Matte Finish**
- Control Panel: Internal Digital Control
- Power Supply: Solar and Replaceable Battery (CR2450 2-Pcs)
- Power On/Off: Full Automatic
- Inside PC Lens: 108 x 108 x 1 mm • Outside PC Lens: 114 x 133 x 1 mm
- Operation Temperature: (-10°C – 65°C) (14°F – 149°F)
- Storage Temperature: (-20°C – 85°C) (-4°F – 185°F)
- Hardhat Adapter Available: Part #HHADAPTER
- Adapter for Plastic Magnifying Lenses
- Digital Low Battery Warning Indicator
- ADF Battery feature with sleep mode
- Use High Quality LCD and multilayer optical interference filter, provides clear view and Permanent UV/IR protection up to DIN 15
- Helmet shell made of high impact resistant Polyamide "Nylon". Ample mask space, especially for ears and bottom flare for neck protection
- EN 175:B, ISO 16321-2, ANSI Z87.1, CSA Z94.3, AS/NZS 1338.1
- Weight: 599g (1.3lbs) • Extra lens provided

SUPREMEVIEW		UPC #	Part #	U/M
SUPREMEVIEW Auto-Darkening Welding Helmet - "True Color"	4 Helmets per Carton	812922017499	SUPREMEVIEW	EA
Adjustable Headgear	One Headgear	812922016843	HEADGEARDJ	EA
SUPREMEVIEW Inside Cover Lens 5-Pack	5 Lens per Pack, 20 Packs per Box	812922017574	SUPREMEVIEWLI	PK